



AMBIT PENDANT LAMP - EU VERSION

TAF ARCHITECTS ON THE DESIGN "Why do you get attracted to certain shapes and not others? With Ambit we worked with the form and proportions in a very thorough and almost meticulous way. There is a dynamic between the linear and rounded shape that creates an attractive outline. A timeless pendant, which never becomes boring to look at. The lampshade is made of a lightweight spun material and the dual-tone, with the inner white, adds a delicate contrast."



Ø 25 cm



Ø 40 cm I5.75"

CANOPY



Ø II cm / 4.95



Beige-











DESIGNED BY / YEAR OF DESIGN

TAF Architechts / 2015

ABOUT THE DESIGNER

TAF Architects is a Stockholm-based design and architecture studio making international headlines within product and interior design.

CATEGORY

Pendant lamp

ENVIRONMENT

Indoor

DESCRIPTION

Classic pendant lamp that is versatile in use. Production is handheld and based on old braizer traditions. The beautiful matt finish gives the lamp a round δ soft feel.

PRODUCTION PROCESS

Made from old braizer traditions, the lamp shade is press spun by hand. Hereafter, the lamp shade is polished and painted by hand.

MATERIAL

Aluminum lamp shade and rubber cord

CORD LENGTH

4000 mm / I57.5"

BULB INCLUDED

CANOPY INCLUDED

Yes - White

DIMMABLE FUNCTION

Yes

CLEANING AND CARE

Clean the lamp with a soft dry cloth. Always switch off the electricity before cleaning.



AMBIT PENDANT LAMP – EU VERSION














LAMP RATING Ø40

Voltage 22O-24OV
Frequency 50/60Hz
IP Rating IP2O
Classification Class II
Socket I x E27

Max. 60W; incandescent lamp; type ${\sf G}$

Max. I3W; self-ballasted

Max. I8W; self-ballasted LED bulb

LAMP RATING Ø25

Voltage 22O-24OV
Frequency 50/60Hz
IP Rating IP2O
Classification Class II
Socket I x EI4

Max. 6OW; incandescent lamp; Type G Max. I3W; self-ballasted; Type G

Max. IIW; self-ballasted LED bulb; Type G

GENERAL STANDARDS & CERTIFICATES - Ø40

 EU/UK
 USA/CANADA
 CHINA

 CE-LVD
 UL
 CCC

 EN 60598-I:2008 + AII:2009
 UL 1598
 GB7000. 201-2008

 EN 60598-2-I:1989
 CAN/CSA C22.2 No. 250.0-08
 GB7000. I-2007

 EN 62493:2010
 GB7000. I-2007

WEEE

GENERAL STANDARDS & CERTIFICATES - Ø25

EU/UK	USA/CANADA	CHINA
CE-LVD	UL	CCC
EN 60598-1:2015	UL 1598	GB7000. 20I-2008
EN 60598-2-1:1989	CAN/CSA C22.2 No. 250.0-08	GB7000. I-2007
EN 69403-9010		

MUUTO