

## Drizzle

### Lightfastness

Note 5-7, ISO 105-B02

### Flame resistance

EN 13 773 class 1  
BS 5867 part 2 type B  
DIN 4102 B1  
SN 198 898 5.2  
NF D 92 507 M1  
UNI 9177 classe 1  
IMO A.471 (XII)

No use of brominated flameretardants

### Quality benefits

Good lightfastness

Permanently flame retardant

Washable

### Environmental benefits

No use of AZO dyes, which may split off carcinogenic acryl amines

No use of dyes containing heavy metals/  
complies with ETAD norm

No content of formaldehyde

No use of brominated flame retardants

We adhere to the limits set by the Danish Environmental Protection Agency's 'List of undesirable substances'

Complies with REACH regulation

For further information  
[www.kvadrat.dk](http://www.kvadrat.dk)



### Drizzle

Design: Aggebo & Henriksen

Type: Sheer curtain

Composition: 50% polyester FR, 50% polyester

Yarn type: Filament

Binding: Plain

Width: App. 300 cm

Weight: App. 150 g/lin.m

Repeat: App. 119 cm (app. 47 inches) from selvedge

Cleaning: Washable at max. 60°C. Half wash load.

Drip drying. Ironing might be necessary when washed at 60°C.

Shrinkage: App. 1%

Stain removal: See special guide

