




www.deprojectinrichter.com 088 - 650 12 84

Polarmoss Flex Element

| PRODUCT SPECIFICATIONS | | |
|--|--|---|
| Product size | Polarmoss Flex Element, small | Polarmoss Flex Element, large |
| | # 40 cm / 15.8 in # | 60 cm / 23.6 in |
| Note that for seamless wall cladding applications, the final area will be about 5–10% smaller than the sum of the individual elements. | S S 60 cm / 23.7 in 60 cm / 23.7 in | T 100 cm / 39.3 in |
| Dimensions | 40 x 60 x 5 cm / 15.8 x 23.7 x 2 in | 60 x 100 x 5 cm/ 23.6 x 39.3 x 2 in |
| Weight | 1.2 kg / 2.6 lb / piece | 3.5 kg / 7.7 lb / piece |
| Quantity in a sales package | 4 pieces | 2 pieces |
| Other sales package content | Hook fastener tape User and installation guide | Hook fastener tape User and installation guide |
| Sales package dimensions | 40 x 60 x 23 cm / 15.8 x 23.7 x 9.1 in | 66 x 111 x 15 cm / 26 x 43.7 x 5.9 in |
| Both sizes | | |
| Base | Felt | |
| Moss fixing done with | Fixing compound | |
| Installation method | With hook fastener tape | |
| Modifiability | Can be cut with scissors or a snap-off knife. | |
| | A single element can be bent to a diameter of ø 50 cm. | |

 $\label{thm:continuous} \mbox{Due to the structure of the natural material, all measurements in the table are approximate.}$





www.deprojectinrichter.com 088 - 650 12 34

Polarmoss Flex Element

TECHNICAL SPECIFICATIONS

Polarmoss Flex Element has been tested for flammability, sound-absorbency, and emissions into indoor air by VTT Expert Services Ltd. and Savonia University of Applied Sciences in Finland.

Flex element is meant for indoor use only and do not need any special maintenance.

The maintenance-free, flame-retardant, and acoustic properties of the handmade product offer a genuine way to introduce nature into the interior spaces of public and private buildings.

| SAFETY | Flame-retardant. Used treatment retards ignition of the underlay material. | |
|-------------|---|--|
| AIR QUALITY | Moss of the product is natural air humidity indicator. Moss dries when the relative humidity of the air falls below 40% and softens again when the relative humidity of the air raises above 40%. | |
| HEALTH | Pigments used for coloring are purity compliant with German BfR IX, European Resolution AP(89)1, EU Directive 94/62/EC, and CONEG. | |
| | No microbe growth area. | |
| | No microbiological emission. | |
| | No emission of volatile organic compounds. | |
| AUTHENTIC | Only 100% natural moss used. | |
| ENVIRONMENT | Hand-picked by our well-trained staff in optimal picking conditions. | |
| | Long intervals between harvesting. | |
| MAINTENANCE | For indoor use only. | |
| | Maintenance free. | |
| | Does not need sunlight or watering or pruning. | |
| ACOUSTICS | Sound-absorbing. Absorbs especially higher speech frequencies. | |